


MAIN APPLICATION	TYPE	MAGNET	
Telecom	64mm	Material	Magnet Size (Square)
		Ferrite	□28.5x□12.5x5mm

ITEM	SPECIFICATIONS	VALUES	TEST CONDITIONS
1	Dimensions	Ø64mm	per mechanical Drawings
2	Impedance	8Ω ±15%	1kHz / 1.0V
3	Nominal Power	1.0 Watts	
4	Max Power	2.0 Watts	
5	Resonant Frequency	400Hz ±60Hz	1.0V
6	Sensitivity (S.P.L.)	86.5dB ±2dB	1W/1m, Average 0.8/1/1.2/1.5kHz
7	Frequency Response	400Hz to 3.5KHz	0.1W/1m; Tolerance Max 20dB
8	THD	2% max	1kHz 0.1W/1m
9	Storage Temperature	-25°C to +80°C guaranteed range for transportation & storage	
10	Polarity	Membrane move forward when positive DC is applied to the '+' terminal	

ITEM	TEST	TEST CONDITIONS	RESULT
11	Rub & Buzz	Rated Power Sin wave (speaker frequency range)	No Buzzes or Rattles.
12	High Voltage Resistance	100VAC / 1mn between terminals and frame.	Must be normal
13	Insulation Resistance	100VDC between terminals and frame.	≥ 1MΩ
14	Load	White Noise at Rated Power for 96h	After 1 hour of rest at room ambient conditions, speakers must meet specs items 2, 5, 6.
15	High Temp.	+60±3°C for 96h (random 20%-50%RH)	
16	Low Temp.	-25±3°C for 96h (random 20%-50%RH)	
17	Humidity	+40±3°C ambient and 90%RH for 96h	

Typical Frequency Response





Property of Seltech. Specifications subject to change without notice. www.seltech-international.com

GASKET	MEMBRANE	BASKET	WEIGHT	REMARKS
Paper	Plastic	ABS + GF	50.5 ±5g	Plastic Membrane Cable+JST BHSR connector

PACKAGING	SPECIFICATIONS	
Carton size:	450x380x160mm	
Qty/Carton:	180 (6 layers of 30pcs)	
Gross Weight:	10.5Kg	

Mechanical Drawings (in mm)



		Part n°	
		SOD2071X8CG2	
REV	DATE	SHEET	
0.2	26/12/2012	1 of 1	RoHS Compliant